



2021 Honda Talon SPECIFICATIONS

Model	Talon 1000X-4 SE (SXS10S4X SE)	Talon 1000X-4 FOX Live Valve (SXS10S4D)	Talon 1000X-4 (SXS10S4X)	Talon 1000R SE (SXS10S2R SE)	Talon 1000X FOX Live Valve (SXS10S2XD)	Talon 1000R FOX Live Valve (SXS10S2RD)	Talon 1000X (SXS10S2X)	Talon 1000R (SXS10S2R)
ENGINE								
Type	999cc liquid-cooled Unicam® longitudinally mounted parallel-twin four-stroke							
Valve Train	OHC, four valves per cylinder							
Bore x Stroke	92.0 mm x 75.15 mm							
Compression Ratio	10.0:1							
Induction	Fuel injection, 46 mm throttle bodies							
Ignition	Full Transistorized							
Starter	Electric							
Driveline	Direct F/R driveshafts							
Transmission	Automatic DCT w/ 6 speeds + reverse & high/low sub-transmission							
Clutch	(2) multiplate wet (DCT)							
SUSPENSION								
Front	Double wishbone; 14.4 in. travel, FOX® Podium 2.5 shocks w/ Live Valve	Double wishbone; 14.6 in. travel, FOX Podium 2.0 shocks w/ Quick Switch 3	Double wishbone; 14.6 in. travel, FOX Podium 2.5 shocks w/ Live Valve	Double wishbone; 17.7 in. travel, FOX Podium 2.5 shocks w/ Live Valve	Double wishbone; 14.4 in. travel, FOX Podium 2.5 shocks w/ Live Valve	Double wishbone; 17.7 in. travel, FOX Podium 2.5 shocks w/ Live Valve	Double wishbone; 14.6 in. travel, FOX Podium 2.0 shocks w/ Quick Switch 3	Double wishbone; 17.7 in. travel, FOX Podium 2.5 shocks w/ Quick Switch 3
Rear	3 Link trailing arm; 15.0 in. travel, FOX Podium 2.5 shocks w/ Live Valve	3 Link trailing arm; 15.0 in. travel, FOX Podium 2.5 shocks w/ Quick Switch 3	3 Link trailing arm; 15.0 in. travel, FOX Podium 2.5 shocks w/ Live Valve	4+ Link trailing arm; 20.1 in. travel, FOX Podium 2.5 shocks w/ Live Valve	3 Link trailing arm; 15.0 in. travel, FOX Podium 2.5 shocks w/ Live Valve	4+ Link trailing arm; 20.1 in. travel, FOX Podium 2.5 shocks w/ Live Valve	3 Link trailing arm; 15.1 in. travel, FOX Podium 2.0 shocks w/ Quick Switch 3	arm; 20.1 in. travel, FOX Podium 2.5 shocks w/ Quick Switch 3
BRAKES								
Front	Two hydraulic calipers w/ 250 mm discs; Electronic Brakeforce Distribution (EBD) system							
Rear	Two hydraulic calipers w/ 250 mm discs; Electronic Brakeforce Distribution (EBD) system							
TIRES								
Front	Maxxis, 28x9x15							
Rear	Maxxis, 28x11x15							
MEASUREMENTS								
Length	154.3 in.	152.6 in.	152.6 in.	125.5 in.	125.5 in.	123.9 in.	123.9 in.	123.9 in.
Width	64.0 in.	64.0 in.	64.0 in.	68.4 in.	64.0 in.	68.4 in.	64.0 in.	68.4 in.
Height	78.1 in.	78.1 in.	78.5 in.	75.6 in.	75.3 in.	75.6 in.	75.3 in.	75.6 in.
Ground Clearance	12.4 in.	12.6 in.	12.8 in.	12.6 in.	12.7 in.	13.0 in.	12.7 in.	13.0 in.
Wheelbase	116.4 in.	116.4 in.	116.4 in.	92.7 in.	87.6 in.	92.7 in.	87.6 in.	92.7 in.
Turning Radius	21.3 ft.							
Fuel Capacity	7.7 gal., incl. 0.9 gal. reserve				7.3 gal., incl. 1.1 gal. reserve			
Cargo Bed Capacity	299 lbs.							
Curb Weight*	1,831 lbs. (1,833 lbs. CA)	1,753 lbs. (1,755 lbs. CA)	1,735 lbs. (1,739 lbs. CA)	1,630 lbs.	1,521 lbs. (1,523 lbs. CA)	1,556 lbs. (1,561 lbs. CA)	1,490 lbs. (1,492 lbs. CA)	1,545 lbs. (1,548 lbs. CA)
OTHER								
Colors	Viper™ Urban Camo	Pearl White/Pearl Red	Metallic Gray	Viper Urban Camo	Pearl White	Metallic Gray	Metallic Orange/Metallic Gray	Pearl White

*Includes all standard equipment, required fluids and full tank of fuel—ready to ride
Meets current CARB and EPA off-road emissions standards
Recommended for riders 16 years of age and older