

ENDURO FACTORY 4 STROKE MY26

EN 

DATA SHEET	250 SEF	300 SEF	450 SEF	500 SEF
Motor	4-stroke DOHC, 4-valve SHERCO technology			
Displacement	248,43cc	303,68cc	449,40cc	478,22cc
Bore and stroke	78 x 52,20 mm	84 x 54,80 mm	95 x 63,40mm	98 x 63,40 mm
Fuel supply	Synerject electronic injection			
Cooling	Liquid cooling with forced circulation			
Starting	Electric starter			
Battery	BS Battery 12V 140A Lithium			
Exhaust	Complete Akrapovič exhaust system	SPES header and Akrapovic silencer	Complete Akrapovič exhaust system	Complete Akrapovič exhaust system
Transmission	6-speed transmission – gear drive primary and chain drive secondary			
Clutch	Hydraulic, multi-disc in oil bath			
Ignition	220 W Alternator			
Chassis	Semi-perimetric high-strength chrome-molybdenum steel			
Fuel tank	9,8 L capacity			
Brakes	Brembo hydraulic brakes, 260 mm Ø (front) - 220 mm Ø (rear)			
Front suspension	Closed cartridge KYB fork with (Factory range) settings and spring rates specific to each model. 48 mm Ø fork legs - 300 mm stroke			
Rear suspension	KYB 50 shock absorber with hydraulic settings and spring rates specific to each model 18 mm Ø - 330 mm stroke			
Front wheel	1.60 x 21'' black anodized Excel rim, Michelin Enduro Medium tire			
Rear wheel	2.15 x 18'' black anodized Excel rim, Michelin Enduro Medium tire			
Wheelbase	1480 mm		1490 mm	
Ground clearance	355 mm			
Saddle height	950 mm			

