

ENDURO XTREM 2 STROKE MY26

EN 

DATA SHEET	250 SE XTREM	300 SE XTREM
Motor	Single-cylinder 2-stroke engine with Electronic control valve and booster	
Displacement	249,32cc	293,14cc
Bore and stroke	66,40 x 72 m	72 x 72 mm
Fuel supply	Keihin PWK 36 carburetor	
Cooling	Liquid cooling with forced circulation	
Starting	Electric starter	
Battery	BS Battery 12V 140A Lithium	
Exhaust	Chromed exhaust pipe and aluminium silencer	
Transmission	6-speed transmission – gear drive primary and chain drive secondary	
Clutch	Hydraulic, multi-disc in oil bath	
Ignition	220 W Alternator	
Chassis	Semi-perimetric high-strength chrome-molybdenum steel	
Fuel tank	10 L capacity	
Brakes	Brembo hydraulic brakes, 260 mm Ø (front) - 220 mm Ø (rear)	
Front suspension	Closed cartridge KYB fork with settings and spring rates specific to each model. 48 mm Ø fork legs - 300 mm stroke	
Rear suspension	KYB 50 shock absorber with hydraulic settings and spring rates specific to each model 18 mm Ø - 330 mm stroke	
Front wheel	1.60 x 21" black anodized Excel rim, Michelin Enduro Medium tire	
Rear wheel	2.15 x 18" black anodized Excel rim, Michelin Enduro Medium tire	
Wheelbase	1480 mm	1480 mm
Ground clearance	355 mm	
Saddle height	950 mm	

