

ENDUROGP 300 SE STEVE HOLCOMBE MY26

EN 

DATA SHEET	300 SE ENDUROGP
Motor	Single-cylinder 2-stroke engine with Electronic control valve and booster
Displacement	293,14cc
Bore and stroke	72 x 72 mm
Fuel supply	Keihin PWK 36 carburetor
Cooling	Liquid cooling with forced circulation
Starting	Electric starter
Battery	Skyrich Battery 12V 140A Lithium
Exhaust	SPES chromed exhaust pipe and Akrapovic Titanium silencer
Transmission	6-speed transmission – gear drive primary and chain drive secondary
Clutch	Hydraulic, multi-disc in oil bath
Ignition	220 W Alternator
Chassis	Semi-perimetric high-strength chrome-molybdenum steel
Fuel tank	10 L capacity
Brakes	Brembo hydraulic brakes, Galfer discs 270 mm Ø (front) - 220 mm Ø (rear)
Front suspension	KYB semi-factory Kashima fork with DLC-coated tubes - 48 mm Ø fork legs - 300 mm stroke
Rear suspension	KYB semi-factory rear shock with triple adjustment and DLC shaf - 18 mm Ø - 330 mm stroke
Front wheel	CNC Machined Blue 4GD hub - 1.60 x 21" black anodized Excel rim, Michelin Enduro tire
Rear wheel	CNC Machined Blue 4GD hub - 2.15 x 18" black anodized Excel rim, Michelin Enduro tire
Wheelbase	1480 mm
Ground clearance	355 mm
Saddle height	950 mm

