

ENDURO FACTORY 2 STROKE MY27

DATA SHEET	12 SE	250 SE	300 SE
Motor	Single-cylinder 2-stroke engine with Electronic control valve and booster		
Displacement	124,81cc	249,32cc	293,14cc
Bore and stroke	54 x 54,50 mm	66,40 x 72 mm	72 x 72 mm
Fuel supply	Keihin PWK 36 carburetor		
Cooling	Liquid cooling with forced circulation		
Starting	Electric starter		
Battery	BS Battery 12V 140A Lithium		
Exhaust	Chromed exhaust pipe and aluminium silencer		
Transmission	6-speed transmission – gear drive primary and chain drive secondary		
Clutch	Hydraulic, multi-disc in oil bath		
Ignition	220 W Alternator		
Chassis	Semi-perimetric high-strength chrome-molybdenum steel		
Fuel tank	10 L capacity		
Brakes	Brembo hydraulic brakes, 260 mm Ø (front) - 220 mm Ø (rear)		
Front suspension	Closed cartridge KYB fork with settings and spring rates specific to each model. 48 mm Ø fork legs - 300 mm stroke		
Rear suspension	KYB 50 shock absorber with hydraulic settings and spring rates specific to each model 18 mm Ø - 330 mm stroke		
Front wheel	1.60 x 21" black anodized Excel rim, Michelin Enduro tire		
Rear wheel	2.15 x 18" black anodized Excel rim, Michelin Enduro tire		
Wheelbase	1465 mm	1480 mm	1480 mm
Ground clearance	355 mm		
Saddle height	950 mm		

